

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Chihiros Aquatic Studio

**Supplier's address:** Nicole Wang, Einsteinstr.2, Neuss, 41464 Neuss, DE

**Model identifier:** WRGB60II

## Type of light source:

|                                                     |                             |                                 |     |
|-----------------------------------------------------|-----------------------------|---------------------------------|-----|
| Lighting technology used:                           | LED                         | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | External adapter connection |                                 |     |
| Mains or non-mains:                                 | MLS                         | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No                          | Envelope:                       | -   |
| High luminance light source:                        | No                          |                                 |     |
| Anti-glare shield:                                  | No                          | Dimmable:                       | Yes |

## Product parameters

| Parameter                                                                                                                                      | Value                     | Parameter                                                                                                                                                  | Value                  |
|------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                             |                           |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  | 65                        | Energy efficiency class                                                                                                                                    | F                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 5 300 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 13 000                 |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     | 67,0                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,28                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                     |
| Outer dimensions without                                                                                                                       | Height                    | Spectral power distribution in the                                                                                                                         | See image in last page |
|                                                                                                                                                | Width                     |                                                                                                                                                            |                        |
|                                                                                                                                                | Depth                     |                                                                                                                                                            |                        |

|                                                                                                                         |       |                                                                    |                                      |  |
|-------------------------------------------------------------------------------------------------------------------------|-------|--------------------------------------------------------------------|--------------------------------------|--|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)                       |       |                                                                    | range 250 nm to 800 nm, at full-load |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -     | If yes, equivalent power (W)                                       | -                                    |  |
|                                                                                                                         |       | Chromaticity coordinates (x and y)                                 | 0,291<br>0,296                       |  |
| <b>Parameters for directional light sources:</b>                                                                        |       |                                                                    |                                      |  |
| Peak luminous intensity (cd)                                                                                            | 1 663 | Beam angle in degrees, or the range of beam angles that can be set | 127                                  |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |       |                                                                    |                                      |  |
| R9 colour rendering index value                                                                                         | 100   | Survival factor                                                    | 1,00                                 |  |
| the lumen maintenance factor                                                                                            | 0,96  |                                                                    |                                      |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |       |                                                                    |                                      |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,95  | Colour consistency in McAdam ellipses                              | 0                                    |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b)  | If yes then replacement claim (W)                                  | -                                    |  |
| Flicker metric (Pst LM)                                                                                                 | 0,0   | Stroboscopic effect metric (SVM)                                   | 0,0                                  |  |

(a) - : not applicable;

(b) - : not applicable;

